

Pleases have a plue pign (4) inside this have	PTO/SB/05 (2/98)
Please type a plus sign (+) inside this box → +	Approved for use through 09/30/2000. OMB 0651-0032
	Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required:	to respond to a collection of information unless it displays a valid OMR control number

UTILITY
PATENT APPLICATION
TRANSMITTAL

to respond to a collection of information unless it displays a valid OMB control number.

Attorney Docket No. TAL/7146.090 (SLA 0322)

First Inventor or Application Identifier Deshpande, Sachin

Title ERROR RESILIENT DIGITAL VIDEO SCRAMBLING

(Only for new nonprovisional applications under 37 C.F.R. § 1.53(b)) Express Mail Label No. EL619332828US

APPLICATION ELEMENTS			ADDRESS	Assistant (Commissioner for Pate Application	nts =
See MPEP cha	apter 600 concerning utility pa	atent application contents.	7.55/1200		n. DC 20231	L. =
2. X Sp	Fee Transmittal Form (e.g ubmit an original and a duplica recification referred arrangement set forth	ate for fee processing) [Total Pages 19] below)	7. Nucleotide (if applicabl	and/or Amino Acid e, <i>ali necessary</i>)	rogram (Appendix) I Sequence Submissi	~~=
	escriptive title of the Inve		a	Computer Read	able Copy	250 400
S .	 Cross References to Related Applications Statement Regarding Fed sponsored R & D 		b	Paper Copy (ide	ntical to computer co	pyr 🗐
- R	Reference to Microfiche Ap	ppendix	С.	Statement verify	ing identity of above	copies
- B	sackground of the Invention	n	ACCO	MPANYING AP	PLICATION PART	s
- B	trief Summary of the Inver	ntion	8. X Assignment Papers (cover sheet & document(s))			
	rief Description of the Dra	wings (if filed)	1 === 37 C	terminal to the second		
_	Petailed Description Claim(s)			9. X 37 C.F.R.§3.73(b) Statement (when there is an assignee) Y Power of Attorney		
	bstract of the Disclosure		10. Englis	h Translation Doc	cument (if applicable)	
	awing(s) (35 U.S.C. 113)	[Total Sheets 5]		ation Disclosure nent (IDS)/PTO-1	Copies of Citations	
4. Oath or D	Declaration	[Total Pages 2]	12. Prelin	inary Amendmen	t	
а	X Newly executed (ork	ginal or copy)		Receipt Postcar		
ь. Г	Copy from a prior ap	plication (37 C.F.R. § 1.63(ld be specifically i	•	
- L	(for continuation/division) [Not	nal with Box 17 completed) e Box 5 below]	14. States	nent(s)	atement filed in prior a atus still proper and d	application,
		INVENTOR(S)	Comis	B/09-12) Guerrich		coned
		ement attached deleting med in the prior application.	110.1	ign priority is clair		i
	see 37 C.F.R.	§§ 1.63(d)(2) and 1.33(b).	16. Other		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
5. Inco	rporation By Reference (u	seable if Box 4b is checked)				
		ior application, from which a n is supplied under Box 4b,	NOTE FOR ITEM	1 & 14: IN ORDER TO	BE ENTITLED TO PAY SA	TALL ENTITY
cons	sidered to be part of the di	sclosure of the accompany	ing IFEES, A SMALL E	ITITY STATEMENT IS PRIOR APPLICATION	REQUIRED (37 C.F.R. § 1.2 IS RELIED UPON (37 C.F.)	17), EXCEPT R. \$ 1.28).
		rporated by reference there	ın. • • • • • • • • • • • • • • • • • • •	THE RESERVE AND THE PERSON NAMED AND ADDRESS OF		
		N, check appropriate box, and s			n a preliminary amendme	ent
	ontinuation Divisiona	Continuation-in-part (CIP) of phor a	oplication No:	<i></i>	
Prior ap	pplication information: Exam			Group / Art Unit:		
		18. CORRESPONDE	NCE ADDRESS	,,	***	
Customer Number or Bar Code Label (Insert Customer No. or Attach bar code label here) Correspondence address below						
Name	Timothy A. I	Long				
		lhauer, McClu	ng & Stenz	el, LLP		
Addman		1600 ODS Tower				
Address	601 S.W. Second Avenue					
City	Portland			57		
Country	U.S.A.	Telephone	503-227-5		503-228-43	
Name (P		A. Long		Vo. (Attorney/Agent)	28,876	
Signature		they (i.	7 . c	Date	9/18/00	
2		wy (1.	7	24.0	3/10/00	

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will yary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

+

PTO/S8/17 (12/99)

Approved for use through 09/30/2000 OMB 0651-0032

Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2000

Patent fees are subject to annual revision Small Entity payments <u>must</u> be supported by a small entity statement, otherwise large entity fees must be paid. See Forms PTO/SB/09-12 See 37 C.F.R. §§ 1.27 and 1.28.

TOTAL AMOUNT OF PAYMENT

WARNING:

(\$)940.00

Complete if Known		
Application Number		
Filing Date	September 18, 2000	
First Named Inventor	Deshpande, Sachin	
Examiner Name		
Group / Art Unit		
Attorney Docket No.	TAT /7146 000 (CT 20222)	

METHOD OF PAYMENT (check one)	FEE CALCULATION (continued)	
The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to. Deposit	3. ADDITIONAL FEES Large Entity Small Entity Fee Fee Fee Fee Fee Code (\$) Code (\$)	Fee Paid
Account Number 03-1550	105 130 205 65 Surcharge - late filing fee or oath	
Deposit Account	127 50 227 25 Surcharge - late provisional filing fee or cover sheet.	
Name Chernoff, Vilhauer	139 130 139 130 Non-English specification	
Charge Any Additional Fee Required Under 37 CFR §§ 1 16 and 1 17	147 2,520 147 2,520 For filing a request for reexamination	
2. X Payment Enclosed:	112 920* 112 920* Requesting publication of SIR prior to Examiner action	
Check Money Other	113 1,840* 113 1,840* Requesting publication of SIR after Examiner action	
FEE CALCULATION	115 110 215 55 Extension for reply within first month	
1. BASIC FILING FEE	116 380 216 190 Extension for reply within second month	
Large Entity Small Entity	117 870 217 435 Extension for reply within third month	
Fee Fee Fee Fee Description Code (\$) Code (\$) Fee Paid	118 1,360 218 680 Extension for reply within fourth month	
101 690 201 345 Utility filing fee 6.90	128 1,850 228 925 Extension for reply within fifth month	
106 310 206 155 Design filing fee	119 300 219 150 Notice of Appeal	
107 480 207 240 Plant filing fee	120 300 220 130	
108 690 208 345 Reissue filing fee	Detical to institute a public use proceeding	
114 150 214 75 Provisional filing fee	Betten to region, versionable	
SUBTOTAL (1) (\$) 690	140 110 240 33	
2. EXTRA CLAIM FEES	141 1,210 241 003	
Fee from	142 1,210 242 605 Utility issue fee (or reissue) 143 430 243 215 Design issue fee	
Extra Claims below Fee Paid Total Claims 23 -20** = 3 X 1.8 = 5.4	144 580 244 290 Plant issue fee	
Independent 5 - 3** = 2 x 78 = 156	122 130 122 130 Petitions to the Commissioner	
Multiple Dependent	123 50 123 50 Petitions related to provisional applications	
**or number previously paid, if greater, For Reissues, see below Large Entity Small Entity	126 240 126 240 Submission of Information Disclosure Stmt	
Fee Fee Fee Fee Fee Description Code (\$) Code (\$)	property (times number of properties)	40
103 18 203 9 Claims in excess of 20	146 690 246 345 Filing a submission after final rejection (37 CFR § 1.129(a))	
102 78 202 39 Independent claims in excess of 3 104 260 204 130 Multiple dependent claim, if not paid	149 690 249 345 For each additional invention to be	
109 78 209 39 ** Reissue independent claims over original patent	examined (37 CFR § 1.129(b)) Other fee (specify)	
110 18 210 9 ** Reissue claims in excess of 20 and over original patent	Other fee (specify)	
SUBTOTAL (2) (\$) 210	*Reduced by Basic Filing Fee Paid SUBTOTAL (3) (\$)	40
SUBMITTED BY Complete (if applicable)		
Name (Print/Type) Timothy A. Long	Registration No (Attorney/Agent) 28,876 Telephone 503-227	7-5631
Signature Line of they !	Date 9/18/00	

Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement: This form is estimated to take 0.2 hours to complete Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS SEND TO. Assistant Commissioner for Patents, Washington, DC 20231

CERTIFICATE OF MAILING BY "EXPRESS MAIL"

Express Mail No.: EL619332828US

Date of Deposit: September 18, 2000

Title: ERROR RESILIENT DIGITAL VIDEO SCRAMBLING

Applicant: Deshpande, Sachin, et al.

I hereby certify that a Utility Patent Application, including Specification (19 pages), with: (1) Fee Transmittal (in duplicate); (2) Utility Patent Application Transmittal; (3) Declaration; (4) Assignment, with Assignment Recordal Cover Sheet; (5) Power of Attorney; (6) Statement Under 37 CFR §3.73(b), with attached copies of Assignment and Power of Attorney; (7) check in the sum of \$940 for the filing fees; and (8) acknowledgment postcard, are being deposited with the United (9) Drawings (FIGS. 1-5) States Postal Service "Express Mail to Addressee" on the date indicated above and is addressed to: Assistant Commissioner of Patents, Box New Application, Washington, D.C. 20231.

Dwight Bergquist-Moody

20

25

30

ERROR RESILIENT DIGITAL VIDEO SCRAMBLING

5 CROSS REFERENCE TO RELATED APPLICATIONS Not applicable.

BACKGROUND OF THE INVENTION

The present invention relates to digital images and, more particularly, to a method of scrambling the images of a digital video sequence that is tolerant of transmission induced data errors.

Conditional access refers to the scrambling or encryption of a signal so that only a user having access to a key can gain access to the original signal. Conditional access permits a provider to supply services only to those users authorized to receive the service and is important to pay television, video-on-demand services, real-time video multi-cast services, and security systems. Conditional access is used in conjunction with video signals transmitted over a variety of communication channels including wireless broadcast, satellite communication, home networks, and the Internet.

Signal scrambling or encryption required for conditional access is problematic when used in conjunction with digital video. Typically, digital video includes a compression process. Without compression, the quantity of data necessary to digitally describe the succession of images making up a video sequence would be so great that transmission or storage would be impractical for many uses. On the other hand, compression produces interdependent data and data losses and errors resulting from transmission can cause an error to propagate to future images of the sequence.

The prior art of video scrambling includes methods that scramble a video signal in the spatial domain. For example, Hobbs, U.S. Patent No. 5,815,572 discloses a number of techniques for scrambling the scan line signals of NTSC

15

20

25

30

(National Television Standards Committee) analog television. One scrambling technique reverses the scan line signal so that the right end of the line becomes the left end and vice versa. Another disclosed scrambling method permutes the order of lines in a block comprising a plurality of scan lines. Similarly, the order of a plurality of blocks of lines making up a field or image can be permuted. In addition, a line might be scrambled by inverting the line signal. For instance, if a higher value of a luminance signal in a scan line represents BLACK and a lower value represents WHITE, the values could be inverted so that the lower values represent BLACK and the higher values represent WHITE. Generally, scrambling signals in the spatial domain significantly affects the statistical properties of the signal making it difficult to apply compression to reduce redundancies in the video signals. In addition, the correlation of video data that is scrambled in the spatial domain can be used as a basis for unscrambling the signal and obtaining unauthorized access to the video.

A second general method of scrambling digital images treats compressed

image data as ordinary data to be encrypted with traditional cryptographic methods. Pinder et al., U.S. Patent No. 5,684,876, disclose a method of applying a block cipher to the payload of MPEG Transport Stream packets. The disclosure indicates that a preferred cipher is the Digital Encryption Standard (DES). Likewise, the Real-Time Transport Protocol (RTP) which is commonly used in conjunction with the User Datagram Protocol (UDP) for digital video transmission supports encryption of packet payload data. However, considerable processing overhead is required to encrypt data at the high rates required for real time video. On the other hand, multimedia data may not be of sufficient value to justify the high cost of data encryption. To reduce the processing overhead, encryption can be applied to selected frames (for example, intra-coded frames) however, such limited encryption may not be sufficiently secure for many applications. The presence of known data such as synchronization and end of block symbols in the MPEG Transport Stream provides a basis for unscrambling the data and obtaining unauthorized access. Further, in some applications it is desirable to transcode the

10

15

20

25

30

data so that the data may be transmitted over a communication channel requiring a data rate different from the data rate of the original encoding. The scrambling key must be available at transcoding points to permit decryption, decompression, re-compression and re-encryption of the data. Making the scrambling key available at a number of transcoding points is inconvenient and can jeopardize the security of the encryption.

One of the inventors of the present invention has proposed a method of video scrambling in which image data is shuffled following transformation. As described by Zeng et al. in the paper EFFICIENT FREQUENCY DOMAIN VIDEO SCRAMBLING FOR CONTENT ACCESS CONTROL, Proceedings of ACM Multimedia, November 1999, digital video may be scrambled by shuffling transform coefficients among the macroblocks making up a horizontal slice of a constituent image. Several scrambling techniques are disclosed providing excellent security for the signal. Since the scrambling is applied to the transformed image data, the statistical properties of the original image and the efficiency of the compression process are essentially unaffected by scrambling. However, video data is often transmitted over noisy communication channels by protocols providing unreliable delivery. As a result, data may be lost during transmission and retransmission or error correction is often impractical. Since packetization of video data proceeds along the horizontal slices of the image, video is susceptible to packet loss. Scrambling data along the direction of packetization may leave the image vulnerable to data errors because of the interdependence of the scrambled data describing the slice.

What is desired, therefore, is a method of image scrambling that provides appropriate security, utilizes reasonable data processing resources, has minimal impact on the efficiency of the compression process, and enables fault tolerant handling of errors or losses in the transmitted data.

SUMMARY OF THE INVENTION

The present invention overcomes the aforementioned drawbacks of the

10

15

20

prior art by providing a method of scrambling a digital image comprising the steps of transforming a value for pixels of the image to an array of transform coefficients and selectively transposing at least one transform coefficient of at least two arrays, the arrays being arranged along an axis substantially orthogonal to an axis of packetization of the transform coefficients. Scrambling the coefficients resulting from transformation requires a reasonable level of processing resources and has minimal impact on the efficiency of the compression process. A number of scrambling options, such as changing the value of the coefficient before scrambling, scrambling luminance or chrominance signals, and scrambling selected images types, provide a selection of levels of security. Further, scrambling the signal in a direction substantially orthogonal to the direction of packetization of the transform coefficients distributes any transmission error in the image reducing the effects of data error or loss on the displayed image.

The error resilient video scrambling can be accomplished by a video encoder comprising a transform coder to transform a plurality of image pixels to an array of transform coefficients; a scrambling buffer storing a first and a second array of transform coefficients representing portions of the image pixels arrayed along an axis substantially orthogonal to an axis of packetization of the transform coefficients; a scrambler selectively transposing a coefficient of the first array to the second array; and a scrambling key identifying coefficients of the first for selective transposition to the second array by the scrambler.

The foregoing and other objectives, features and advantages of the invention will be more readily understood upon consideration of the following detailed description of the invention, taken in conjunction with the accompanying drawings.

20

25

30

5

BRIEF DESCRIPTION OF THE DRAWINGS

- FIG. 1 is a schematic representation of the constituent data of a digital video sequence.
- FIG. 2 is a block diagram of a video encoder incorporating scrambling according to the present invention.
- FIG. 3 is a schematic representation of block based transform coding.
- FIG. 4 is a schematic representation of a portion of a transform coded image.
- FIG. 5 is a block diagram of a video decoder and descrambler.

10 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to FIG. 1, a digital video sequence 10 comprises a succession of images 14 or pictures transmitted or stored as data packets in a data stream. Signals representing the images are captured by a camera or other device, converted to digital data, compressed, packetized, and transmitted or stored. At a display point, the data is decompressed and converted to signals which are used to control the display device. The quantity of data required to digitally describe the images of a video sequence is so great that digital video would be impractical for many applications without data compression. The objective of compression is the reduction of spatial and temporal redundancy in the data describing the succession of images.

Temporal redundancy is typically addressed by inter-coding or identifying the differences between successive images. If a reference image is available, a target image can be produced from the reference image and the differences between the two images. Therefore, it is only necessary to store or transmit the reference image and the differences between the reference image and any target images predicted therefrom. FIG. 1 is a schematic representation of the data of a video sequence illustrating division of the data for the purpose of block based transform coding by a video encoder utilizing a discrete cosine transform (DCT) as specified in the JPEG, MPEG-1, MPEG-2, and H.26X specifications. This encoder embodiment is described for purposes of illustration and not by way of

15

20

25

30

limitation and the methods of the invention can be applied to other encoding processes, including wavelet-based encoding. An MPEG-2 digital video sequence 10 typically comprises a succession of Groups of Pictures or GOP 12 which, in turn, comprise a succession of coded images 14. While the number of images in a GOP 12 is not specified, a typical GOP includes approximately 15 images. Each GOP 12 includes an intra-coded (I) image 16 which is encoded as a discrete image, independent of other images, and requiring no additional information for decoding. I-images 16 provide access points to the stream of data permitting operations such as fast forward. I-images 16 also provide fault tolerance permitting access to the video data stream at the next I-image if data for several images are lost. In addition, the GOP 12 typically includes forward predicted (P-) images 17 which are predicted from an earlier image, and bidirectionally predicted (B-) images 19 that are predicted from both earlier and later I- or P-images.

Each image 14 of the sequence is represented by packets of data capturing horizontal sections or slices 18 (indicated by brackets) of the image 14. While the data may represent either a video field or video frame, either arrangement of data is referred to herein as an image or picture. The sizes of slices 18 are arbitrary and for MPEG video may start anywhere in the image. On the other hand, a slice 18 for ATSC (Advanced Television Systems Committee) digital television must start at the left edge of an image. The slice 18 is the fundamental unit of synchronization for the variable length and differential coding used in compression. A slice 18 or GOB (group of blocks) is a horizontal division of the image comprising at least one macroblock 20 and, typically, a horizontal strip of contiguous macroblocks. Macroblocks 20 are fundamental units of the image and are used in the motion estimation and compensation process that underlies intercoding. Each macroblock 20 comprises four luminance blocks 25 and the chrominance blocks 26 that occupy the same spatial area of the image. The number of chrominance blocks 26 included in a macroblock is determined by the chrominance sub-sampling scheme used in the video coding process. In effect,

10

15

20

25

30

the image 14 is segmented horizontally by slices 18 and vertically by columns of macroblocks 22 (indicated by a bracket) which, in turn, comprise vertical columns of blocks 25 or 26. The Real-Time Transport Protocol (RTP) is commonly used for transferring digital video data. Generally, the packet payload formats recommended by RTP facilitate packetization along the axis of the slices 18 or GOBs and synchronization words useful to recover from data errors and loss are available at the GOB or slice level.

In addition to temporal redundancies characteristic of successive images, individual images typically include spatial redundancies in the similarity of adjacent pixels in flat areas of the image and dominant frequencies in patterned areas. Spatial redundancy is reduced by intra-coding of individual images through the steps of transformation, quantization, and entropy encoding. Transformation applies an invertible transform to convert spatial domain data describing the image to a collection of coefficients describing the image in another domain, usually the frequency domain. For MPEG-2 transform coding the pixels of the individual luminance and chrominance signals are divided into 8X8 blocks. As illustrated in FIG. 3, a transform module 46 applies the DCT transform to blocks 24 of pixels, transforming the luminance or chrominance values of the pixels to an array of transform coefficients 80.

The succession of images 14 making up a video sequence 10 are captured by a camera or other device usually as analog signals representing the red, green, blue components of the light reflected by an object. The analog signals are converted to digital signals and the red, green, and blue values of the image pixels are typically converted to a luminance and two chrominance values. Typically, the chrominance of the image is sub-sampled because the human visual system is more sensitive to image luminance than chrominance. In addition to signal conversion, a preprocessor may arrange the image data so that images will be encoded in the order of their decoding. Since some of the images will be predicted from other images, the reference images must be decoded before the decoding of predicted images can proceed.

20

25

30

Referring to FIG. 2, the pre-processed digital data representing an image are input 42 to the video encoder 40. Individual images of the sequence are either inter-coded or intra-coded as determined by the order in which they are input to the encoder 40. A switch 44 at the encoder input selects the encoding path appropriate for each image. For an intra-coded image the switch 44 directs the image to the transform module 46. Pixels from either the luminance or chrominance input data for the image 14 are mapped to 8 X 8 arrays of pixels or blocks 24. In the transform coder 46, the DCT is applied to the pixels of the block 24 and the luminance or chrominance values of pixels are transformed to an 8 X 8 array of transform coefficients 80 representing the frequencies of the block, as illustrated in FIG. 3. The coefficient 82 in the upper left corner of the block represents the DC coefficient for the block. Coefficients vertically below the DC coefficient 82 represent increasing vertical spatial frequencies and coefficients to the right of the DC coefficient represent increasing horizontal spatial frequencies.

A DCT-based transformation applied to a typical image produces zero, or very small, coefficient values for many of the higher spatial frequencies. Coincidently, the human visual system is less sensitive to higher spatial frequencies so the zero coefficients and many of the smaller coefficients can be coarsely defined or eliminated without noticeable degradation of image quality.

The data representing the transformed image is accumulated in a transform buffer 48 at the output of the transform module 46. A schematic representation of a transformed luminance signal for a portion of an image 14 is illustrated in FIG. 4. Each 8X8 pixel block is represented by an 8X8 array or block of transform coefficients 100 (indicated by a bracket). Macroblocks of transform coefficients 102 (boundaries indicated by a bracket) comprise the four arrays of transform coefficients 100 representing the four pixel blocks of a luminance macroblock and the arrays of transform coefficients representing the chrominance of the area of the image occupied by the luminance block. FIG. 1 illustrates a subsampling of the image chrominance with two chrominance blocks 26 included in the macroblock 20. In general, the image 14 is represented by columns of

10

15

20

25

30

transform coefficient arrays 104 (indicated by brackets) which are arranged orthogonal to slices 106 of coefficient macroblocks 102. The coefficient data for a column of blocks 104 is input to a scrambling buffer 50 of a scrambler 52. The scrambler 52 selectively transposes transform coefficients between the arrays in the column of arrays according to a shuffling table 54 which is controlled by a cryptographic key 56. A coefficient of a first array of an array column 104 is exchanged for a coefficient typically occupying the same band or frequency location in a second array of the column. For example, the DC coefficients 82 and 108 of two coefficient arrays 100 and 112 of a column of coefficient blocks might be transposed or the coefficients of several arrays of the column may be transposed by rotation through several blocks. For example DC coefficient 82 might replace DC coefficient 109 which, in turn, might replace DC coefficient 108 which may be used to replace coefficient 82. In addition, AC coefficients, for example coefficients 110 and 111, for one or more frequency locations may be permuted according to the same or a different shuffling scheme. Likewise, DC and AC coefficients may be permuted for the chrominance coefficient arrays. In addition, the transform coefficients may be altered. For example, the sign of a coefficient might be reversed if the coefficient has a predetermined relationship to a threshold value. The signs of AC coefficients may be inverted or DC coefficients may be assigned a negative sign if the value of the coefficient exceeds a threshold value. For additional security, the transform coefficients can be scrambled along macroblock columns where the coefficients are transposed horizontally as well as vertically. One luminance macroblock provides four similar coefficient positions (four arrays) within which coefficients can be transposed. The scrambler 52 scrambles the transform coefficient data along the columns of arrays 104 in a direction substantially orthogonal to the direction of data packetization which proceeds generally in the direction of the axis of the slices 106.

Following transformation and scrambling, the scrambled transform coefficients are quantized 56. Since the human visual system is less sensitive to higher

10

15

20

25

30

spatial frequencies, weighting may be applied during the quantization process to further minimize the coefficients representing higher frequencies. Typically, quantization of video images uses up to eleven bits to represent the DC block coefficient and significantly fewer bits to represent the higher frequency coefficients. However, since scrambling is applied to the transformed data and transform coefficients from the same frequency locations in the arrays are transposed, scrambling does not affect the quantization process. Quantization is a lossy compression process and much of the data compression is accomplished in the quantizer 56.

If the input image 42 is to be an inter-coded (P or B) image the switch 44 selects the inter-coding position and the incoming image or target image is sent to the motion estimation and compensation unit 58 for comparison to one or more reconstructed reference images from which the target image is to be predicted. When a reference image has been quantized 56, a copy of the quantized data is sent to a decoder section 60 (indicated by a bracket) of the encoder 40. In the decoder section 60, the image is reconstructed by dequantization 62, unscrambling 64, and inverse transformation 66 and the reconstructed image stored in a reference frame storage 68. The descrambler 64 reverses the transform coefficient shuffling performed by the scrambler 52 using the same shuffling table 54 and key 56 used by the scrambler to shuffle the coefficients.

To encode a target P-image, the motion estimation and compensation unit 58 compares a reference I-image in the reference frame storage 68 to the input target image to determine forward motion vectors. In the motion estimation and compensation unit 58 macroblocks of the current image are moved incrementally over a search range in the reference image until the greatest correlation between the current macroblock and a corresponding region in the reference image is obtained. Motion vectors indicating the necessary horizontal and vertical movements of matched region are calculated and recorded in the header of the macroblock in the data stream. The motion vectors are transmitted to the decoder for use in conjunction with reference image data in decoding the predicted

10

15

20

25

30

images. The reference I-image is shifted by the motion vectors to construct a predicted P-image which is then subtracted 69 from the input image to produce a prediction error. The prediction error or residual data is input to the transform coder 46 and quantizer 56 and spatially coded. The prediction error may also be scrambled in the scrambler 52. In general, scrambling the coefficients of I-images 16 will render any predicted P- or B-images difficult to perceive because of the data dependency of the predicted frames. While the P- and B-images may not need to be scrambled, the motion of the video sequence is often visible unless the motion vectors are scrambled. Motion vectors can be scrambled by assigning signs to the vectors exceeding a threshold or the vectors can be shuffled. The prediction error is also reconstructed in the decoder section 60 and added 70 to the predicted P-image to create a locally decoded P-image that is stored in the reference image storage 68 for use as a reference image in encoding appropriate P- or B-images.

If the input image is to be coded as a B-image, the motion estimation and compensation unit 58 compares the target B-image with the reference images that precede and follow the target image and which are stored in the reference image storage 68. Forward and backward motion compensation is performed to produce two predicted B-images. These are subtracted from the target B-image and the data from either the forward or backward motion compensation that represents the least difference is spatially coded and sent with the motion vectors.

Entropy coding 72 is applied to the arrays of transform coefficients following quantization 56. Referring to FIG. 3, typically, a block of coefficients is scanned in a zig-zag pattern 84 that maximizes the runs of zero value coefficients. The entropy encoder 72 applies lossless compression methods such as variable length encoding and run length coding to further reduce the quantity of data. Variable length encoding identifies common patterns in the data and uses codes to identify frequently occurring patterns. Run length encoding uses a unique code word to identify a repeating pattern of bits in the data stream and outputs the number of bits in the pattern rather than the individual bits. The motion vectors and other

10

15

20

25

30

macroblock and slice header information are typically added to the data stream at the entropy encoder 72.

The video elementary data stream at the output of the entropy encoder 72 is input to a packetizer and buffer unit 74. For convenience, the elementary stream may be broken into data blocks by the packetizer and buffer unit 74 to form a packetized elementary stream (PES). While the data stream follows the zig-zag pattern through the blocks or arrays of transform coefficients, the axis of the packetization is generally along the horizontal axis of the slices 18 of the images.

Video data systems are typically designed to utilize data at a near constant rate. However, the data rate output by the entropy encoder 72 varies because of the differing quantities of data required to encode the various images. The buffer of the packetization and buffer unit 74 smooths the flow of elementary stream data 74 from the encoder 40 and provides a mechanism for controlling the encoding rate. Following encoding by the video encoder 40, timing information is added to the packetized elementary stream and video, audio, and data elements of the video program are combined by a program or transport stream multiplexer to produce a program data stream for storage or a transport stream for broadcasting.

To display the video sequence, the elements of the program or transport data streams are separated and decoded. Referring to FIG. 5, the scrambled video elementary stream 122 resulting from the separation of the program or transport stream is decoded in a video decoder 120. In the decoder 120 the encoding process is reversed to produce signals for controlling the operation of a display, transcoding device, or other information sink. Elementary stream packets 122 are input to a buffer and depacketizer unit 124 to smooth the data flow to the decoder and remove the elementary stream packetization information. The resulting data stream is input to an entropy decoder 126 that recovers the motion vectors, quantization parameters, and other data 128 from the encoded data stream and reverses the entropy encoding. A de-quantizer 130 reverses the quantization process of the encoder 40 to produce blocks of transform coefficients that are

15

20

25

stored in the frame buffer 132. Data for columns of image blocks are input to a descrambler 134 where shuffling tables 136, duplicating those used in encoding the data, are used to reverse the scrambling of the transform coefficients. The key 56 used in scrambling the data and obtained from the encoder 40 is used to establish the shuffling table 136 for unscrambling the data stream. Following unscrambling, the transform coefficients are input to the inverse transform module 138 which applies the inverse transform to produce luminance and chrominance data describing an image that approximates the original image. If the data represents a B- or P-image the switch 140 selects the inter-coding position and a motion compensation unit 142 utilizes the motion vectors obtained from the entropy decoder 126 to determine the differences between the target image and the reference image. The difference data is added 144 to the data for the reference image to produce the data describing the digital image 146 which may be further processed to create signals appropriate to operate a display or other device. Since scrambling is applied to transform coefficients and occurs along an axis orthogonal to the axis of elementary stream data packetization, the scrambling has minimal effect on compression efficiency and the effect of any data loss or error is distributed more widely in the image producing fewer visually noticeable effects on the reconstructed image.

All the references cited herein are incorporated by reference.

The terms and expressions that have been employed in the foregoing specification are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims that follow.

CLAIMS

5

10

20

30

The invention claimed is:

- 1. A method of scrambling a digital image comprising the steps of:
 - (a) transforming a value of pixels of said image to an array of transform coefficients; and
 - (b) selectively transposing at least one transform coefficient of at least two said arrays, said at least two arrays arranged along an axis substantially orthogonal to an axis of packetization of said transform coefficients.
- 2. The method of claim 1 wherein said transposed transform coefficients occupy corresponding positions in said at least two arrays.
- 15 3. The method of claim 1 wherein said transformed value of said image pixels is a luminance of said pixels.
 - 4. The method of claim 1 wherein said transformed value of said image pixels is a chrominance of said pixels.
 - 5. The method of claim 1 further comprising the step of altering a value of a transposed transform coefficient.
- 6. The method of claim 1 further comprising the step of altering a sign of a
 transposed transform coefficient if a value of said transform coefficient has a predefined relationship to a threshold value.
 - 7. The method of claim 1 further comprising the step of selectively transposing at least one transform coefficient of at least two said arrays along an axis substantially parallel to an axis of packetization of said transform coefficients.

- 8. A method of scrambling a digital image comprising the steps of:
 - (a) mapping a plurality of pixels of said image to a pixel block;
 - (b) transforming a value of said pixels of said pixel block to an array of transform coefficients; and
- (c) selectively transposing a transform coefficient of at least two said arrays of transform coefficients arranged along an axis substantially orthogonal to an axis of packetization of said array.
- 9. The method of claim 8 wherein said transposed transform coefficients occupycorresponding positions in said at least two arrays.
 - 10. The method of claim 8 wherein a luminance value of said pixels is transformed to said array of transform coefficients.
- 15 11. The method of claim 8 wherein a chrominance value of said pixels is transformed to said array of transform coefficients.
 - 12. The method of claim 8 further comprising the step of altering a value of said transposed transform coefficients.
 - 13. The method of claim 8 further comprising the step of altering a sign of a transposed transform coefficient if a value of said transform coefficient has a predefined relationship to a threshold value.
- 25 14. The method of claim 8 further comprising the step of selectively transposing at least one transform coefficient of at least two said arrays along an axis substantially parallel to an axis of packetization of said transform coefficients.

20

10

15

20

30

- 15. A method of scrambling a sequence of digital images comprising the steps of:
 - (a) selecting at least one said image for coding as a discrete image;
 - (b) transforming pixels of said discrete image to a plurality of arrays of transform coefficients;
 - (c) selecting a plurality of said arrays arranged substantially along a first axis of said image;
 - (d) replacing a coefficient of a first of said selected arrays with a coefficient of a second of said selected arrays, said coefficients of said first and said second arrays being identified by a cryptographic key; and
 - (e) packetizing said coefficients of said plurality of arrays substantially along a second axis substantially orthogonal to said first axis.
- 16. The method of claim 15 wherein said coefficient of said second selected array occupies a same position in said second selected array as said replaced coefficient occupies in said first selected array.
 - 17. The method of claim 15 wherein a luminance representation of said pixels is transformed to said array of transform coefficients.
 - 18. The method of claim 15 wherein a chrominance representation of said pixels is transformed to said array of transform coefficients.
- 19. The method of claim 15 further comprising the step of altering a value ofcoefficient of said second of said selected arrays.
 - 20. The method of claim 15 wherein said selected plurality of arrays arranged substantially along a first axis of said image includes a first and a second pluralities of said arrays, said first and said second pluralities aligned with said first axis but displaced from each other along said second axis.

10

15

20

25

- 21. The method of claim 15 further comprising the steps of:
 - (a) selecting at least one image for prediction from said discrete image;
 - (b) determining a difference between said predicted image and said discrete image;
 - (c) transforming pixels of said difference to a plurality of arrays of transform coefficients;
 - (d) selecting a plurality said arrays arranged substantially along a first axis of said image;
 - (e) replacing a coefficient of a first of said selected arrays with a coefficient of a second of said selected arrays, said coefficients of said first and said second arrays being identified by a cryptographic key; and
 - (f) packetizing said coefficients of said plurality of arrays substantially along a second axis substantially orthogonal to said first axis.

22. An image encoder comprising:

- (a) a transform module to transform a plurality of image pixels to an array of transform coefficients;
- (b) a scrambling buffer storing a first array and a second array of transform coefficients, said first and said second arrays representing portions of said image pixels arrayed along an axis substantially orthogonal to an axis of packetization of said transform coefficients;
- (c) a scrambler selectively transposing a coefficient of said first array to said second array; and
- (d) a scrambling key identifying a coefficient of said first array for selective transposition to said second array by said scrambler.

-17-

- 23. A decoder for a digital image comprising:
 - (a) a scrambling key identifying a scrambling coefficient of a first array of

- transform coefficients for selective transposition to a second array of transform coefficients;
- (b) a descrambling buffer storing said first and said second arrays of transform coefficients, said first and said second transform coefficient arrays representing pixels of said digital image arrayed along an axis substantially orthogonal to an axis of packetization of said transform coefficients;
- (c) a descrambler to selectively transpose said scrambling coefficient of said first array to said second array of coefficients as described by said scrambling key; and
- (d) an inverse transform module to transform said array of said transform coefficients to a plurality of pixels of said digital image.

5

10

ABSTRACT OF THE DISCLOSURE

A method and an apparatus for error resilient, digital image scrambling are disclosed. Error resilience scrambling is produced by shuffling transform coefficients between arrays of coefficients arranged along an axis substantially orthogonal to the axis along which packetization of the coefficients proceeds. Scrambling transform coefficients requires a reasonable level of processing resources and has minimal impact on the efficiency of the compression process. Shuffling can be performed in a number of ways to provide good access security and a variety of security. Scrambling the image data in a direction substantially orthogonal to the direction of packetization of the transform coefficients distributes any transmission error in the image reducing the effects of data error or loss on the displayed image.




FIG. 1 (PRIOR ART)




FIG. 2




FIG. 3 (PRIOR ART)




FIG. 4




FIG. 5

the specification of which:

DECLARATION

As the below named inventors, we hereby declare that:

Our residences, post office addresses and citizenship are as stated below next to our names respectively.

We believe that we are the original, first and only inventors of the subject matter which is claimed and for which a patent is sought on the invention entitled

ERROR RESILIENT DIGITAL VIDEO SCRAMBLING

[X]	is attached hereto. was filed on Application Serial No and was amended o	as o n (if applicable).	
	fied specification, incl	ave reviewed and understand the uding the claim(s), as amended l	
	of this application in a	o disclose information which is maccordance with Title 37, Code o	
119 of any for have also ide	oreign application(s) for entified below any fore	iority benefits under Title 35, Unior patent or inventors' certificate eign application for patent or invente application on which priority in	listed below and entor's certificate
Prior Foreigr	n Application(s)		Priority Claimed
(Number)	(Country)	(Day/Month/Year Filed)	[] Yes [] No
(Number)	(Country)	(Day/Month/Year Filed)	[] Yes [] No
	ereby claim the benefi application(s) listed be	it under 35 U.S.C. § 119(e) of an low.	y United States
(Application	Serial No.)	(Filing Date)	

We hereby claim the benefit under Title 35, United States Code, § 120, of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Ser. No.) (Filing Date) (Status) (patented, pending, abandoned)

We hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Dated: 9/	12/2000	S. G. Deshpande		
•		Sachin Deshpande		
Residence		Vancouver, Washington		
Citizenship		India		
Post Office Address		16900 S E 26 th Drive, Apt. T 131		
		Vancouver, Washington 98683		
Dated: 9	14/20vi	Wing 3V		
		Wenjun Zeng		

Residence Citizenship Post Office Address

Peoples Republic of China 18611 S E 24th Street

Vancouver, Washington

20

Vancouver, Washington 98683

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE PATENT APPLICATION EXAMINING OPERATIONS

Applicant:

Deshpande et al.

Group Art Unit:

Serial No:

Examiner:

Filed:

herewith

Title:

ERROR RESILIENT DIGITAL VIDEO SCRAMBLING

POWER OF ATTORNEY

I, Jeffrey B. Sampsell, declare that I am the Vice President of Sharp Laboratories of America, Inc., a Washington corporation, and I am authorized to execute this document on its behalf. Sharp Laboratories of America, Inc., is the assignee of the entire right, title and interest in the above-referenced patent application and hereby appoints Jacob E. Vilhauer, Jr., Reg. No. 24,885, Charles D. McClung, Reg. No. 26,568, Dennis E. Stenzel, Reg. No. 28,763, Donald B. Haslett, Reg. No. 28,855, William O. Geny, Reg. No. 27,444, J. Peter Staples, Reg. No. 30,690, , Kevin L. Russell, Reg. No. 38,292, Nancy J. Moriarty, Reg. No. 40,733, Bruce W. DeKock, Reg. No. 40,585, and Timothy A. Long, Reg. No. 28,876 all members of the firm of CHERNOFF, VILHAUER, McCLUNG & STENZEL, 1600 ODS Tower, 601 S W Second Avenue, Portland, Oregon 97204, Telephone No. (503) 227-5631, its attorneys, jointly and individually, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Dated:

Name:

Jeffred B. Sampsell, Ph.D.

Company:

Vice President Sharp Laboratories

of America, Inc.